



Saturn

1000-E UPT

Castles Technology's newly designed SATURN1000-E UPT makes your checkout process a lot easier. In addition, it comes with several optional features including 4G LTE, Wi-Fi, Bluetooth, microphone, front camera, and barcode reader. The SATURN1000-E UPT is based on a secure Android platform and has integrated contactless reader function with a 5" full touchscreen. Lastly, this self-service solution provides a secure and reliable transaction environment which is perfect for vending machines, coolers, and other unattended applications.

Secure Android Platform

5" Color Touch Screen

Front Camera (Optional)

Barcode Reader (Optional)

FEATURES & BENEFITS



Unprecedented Security and Certifications

- PCI PTS 5.x
- EMV Contact/ Contactless Lv1
- EMV Contact Lv2
- Contactless Scheme Certifications (Paypass, Paywave, ExpressPay, D-PAS, J-Speedy, QPBOC...)



Incredibly Adaptable

- Optional barcode reader
- Accepts all payment types
- Flexible to integrate business applications



Exceptional Performance

- High Security Processor
- Operable under extreme conditions
- Secure Android architecture OS

SATURN 1000-E UPT



SPECIFICATIONS

			SATURN1000-E UPT	
Processor			High Speed Quad-Core Processor plus Secure MCU	
Memory	Flash/RAM		8GB/1GB (Up to 16GB/2GB)	
Operating System			Android v7.x	
Display			5" Color TFT LCD with Capacitive Touch Panel 1280 x 720 Pixels	
Card Reader	Magnetic Stripe	User Card	ISO 7810, 7811, 7813 Triple Track, Bi-Directional	
		Contact Card	ISO 7816 ID-1 1.8V/3V/5V T=0, T=1	
	Contactless (Optional)	SAM Card	2	
		SIM Card	2	
Communications Interface Options	Wire	RS-232 USB MDB Antenna		
	Wireless	4G LTE Wi-Fi Bluetooth Ethernet		
Indicators	Audio		Speaker Audio Jack (4-Pole) Microphone	
Keypad			Virtual Keypad (Support PIN on Touch)	
Software			SDK KMS TMS GDB CTOS library ISO 8583 library Crypto library	
Crypto			TRNG DES T'DES AES RSA MK/SK DUKPT	
Power Supply	DC		9-60V	
Dimensions (L x W x H)			191.8 x 110 x 65.6 mm	
Weight			600 g	
Environment	Operating Temperature		0°C to 50°C	
	Storage Temperature		-20°C to 70°C	
	Operating Humidity		5% to 90% non-condensing	
	Storage Humidity		5% to 90% non-condensing	
	IP Ingress Protection		IP 54	
		IK Shock Protection		IK 08
Certification			PCI PTS 5.X EMV L1/L2 payWave PayPass ExperssPay D-PAS Interac Flash J-Speedy FeliCa UnionPay UICS TQM PBOC L1/L2	
Optional Features			5M Pixels Front Camera Barcode Reader	